

# RJ45 Jack, Waterproof

## Panel mount

### Specification

Data  
 100 Base T, 100 Base T and 1000 Base T Networks  
 Cat 5E per TIA/EIA 568B  
 Class D per ISO/EIC 11801

Category: Cat.5, Cat.5E, Cat.6

Material  
 Connector body: ABS/PBT/PA66 UL94V-0 1/8"  
 Contact: Brass 4u"-20u" Gold plated




Temperature range: -20 — +80 C  
 Waterproof IP67  
 Durability 500 cycles  
 Flame test UL/CAS FT4  
 Thermal shock 5 cycles at -20 — +80 C / 5  
 Salt Spray 48 hrs / 48

**CGR RJ - 5E P FF J - S C 7 - 001**

1 2 3 4 5 6 7 8 9

	<b>Description</b>	<b>Details</b>	<b>Code</b>
1	Connector	RJ45 or Shield RJ45	RJ or RJS
2	Category	Cat. 5E	5E
3	Connector Type	Panel Mount	P
4	Connector Gender	Jack Connector	FF
5	Assembly Style	110D or RJ45 Jack	B or J
6	Mating Style	Lock or Screw	L or S
7	Backs shell	Circular	C
8	Waterproof Rating	IP67	7
9	Version		001, 002

### RJ45 Jack Panel Mount/Screw type



### RJ45 Jack Panel Mount/Lock Bayonet

